

A KOHLER COMPANY

ACCORD_{TM}

Features

- Handicap seat mounts directly to back wall of bath surround and rests on apron
- Stainless steel grab bars 1-1/2" (3.8 cm) OD
- Compression molded from Sterling's exclusive solid Vikrell_® material
- Modular 4-piece design
- · Lightly pebbled bottom surface for sure footing
- Pivot "snap together" installation
- · Caulkless installation
- Wall surround available with smooth finish or glazed tile appearance
- 60" (152.4 cm) x 31-1/4" (79.4 cm) x 73-1/4" (186.1 cm) complete unit rough-in dimensions include flanges
- 60" (152.4 cm) x 30" (76.2 cm) x 72" (182.9 cm) complete unit finished dimensions
- 15" (38.1 cm) bath depth (floor to top of dam)


Codes/Standards Applicable

Specified model meets or exceeds the following:

- ADA
- ANSI Z124.1.2
- IAPMO/UPC
- ASTM E162
- ASTM E662
- ICC/ANSI A117.1

60" (152.4 cm) ADA COMPLIANT BATH/SHOWER SYSTEM **71140115**

ALSO 71140125, 71240115, 71240125





Colors/Finishes

- 0: White
- Other: Refer to Price Book for additional colors/finishes

Specified Model

Model	ADA Compliant Complete Unit Description	Colors/Finishes	
71140115	Tile finish wall surround and ADA compliant bath, left drain	□ 0	☐ Other
71140125	Tile finish wall surround and ADA compliant bath, right drain	□ 0	☐ Other
71240115	Smooth finish wall surround and ADA compliant bath, left drain	□ 0	☐ Other
71240125	Smooth finish wall surround and ADA compliant bath, right drain	0	☐ Other

SterlingPlumbing.com

Visit us online for fixture color choices, detailed product information, color photos, installation instructions, care guides, and warranties. Sterling offers additional lines of plumbing products to complement the Sterling product you've chosen. Sign up for the Sterling monthly e-newsletter which showcases our latest product innovations. You may also call our Sterling Plumbing Answer Center from within the USA at 1-888-STERLING in addition to consulting with your local dealer. Sterling. Strong. Professional. Design.

ACCORD_{TM}

Technical Information

Fixture*:	basin area	top area			
Bathing well	46-1/4" (117.5 cm) x 20-1/2" (52.1 cm)	52-1/4" (132.7 cm) x 22-1/2" (57.2 cm)			
To overflow	water depth	capacity			
	11" (27.9 cm)	34 gal (128.7 L)			
* Ai					

^{*} Approximate measurements for comparison only.

Model	door maximum width	door maximum height
71140115 71140125 71240115 71240125	56-3/4" (144.1 cm)	56-1/2" (143.5 cm)

Installation Notes

Install this product according to the installation guide.

To be ADA compliant, install according to the requirements of the Americans with Disabilities Act (ADA). Use only ADA compliant components.

Studs should be positioned roughly as shown for wall surround installation.

Bath cannot be installed without the wall surround.

